DATASHEET · CHECKWEIGHERS

LOMA SYSTEMS CW3 RUN-WET 1500L datasheet

Checkweigher

AT A GLANCE **Weighing range 10–1500 g · Belt speed 115 m/min · Belt width 200–300 mm**

Maker: LOMA SYSTEMS · Verified: 2026-10-01

IP69-tested CW3 RUN-WET washdown checkweigher for packaged or semi-packaged food before final sealing, in the 1500L size for packs up to 1,500 g.

Specifications

SPEC	VALUE
PERFORMANCE	
Weighing range	**10–1500 g**
Belt speed	**115 m/min**
FORMAT	
Belt width	**200–300 mm**
CONFIGURATION	
Reject systems	**pusher, dual air blast**
INSTALLATION	
Protection rating	**IP69**
UTILITIES	
Power supply	**110 or 230 V, 1-phase, 50 or 60 Hz**

Key features

- Tested to IP69 for high-pressure, high-temperature washdown
- Runs immediately after washdown without drying
- Multilevel password protection via RFID tags
- Auto-zero compensation for spilled product on the weighing platform
- Approved systems to OIML R51 and MID (EC TAC)
- Data via USB, Ethernet, TRACS and OPC-UA

Formats and options

Typical products	meat, poultry and fish, fruit, vegetables and nuts, dairy and egg products, convenience food
Options	TRACS data logging software