

WIPOTEC HC-M-WD datasheet

Checkweigher

AT A GLANCE Speed 250 packs/min · Precision (standard deviation) 0.1 g · Scale division 0.05 g

Maker: WIPOTEC GmbH · Verified: 2026-10-01

Wash-down version of the HC-M checkweigher in hygienic stainless steel design, with IP69K protection for all components. WIPOTEC rates it at up to 250 pcs/min.

Specifications

SPEC	VALUE
PERFORMANCE	
Speed	250 packs/min
Precision (standard deviation)	0.1 g
Scale division	0.05 g
FORMAT	
Belt width	150–350 mm
INSTALLATION	
Protection rating	IP69K
Machine weight	250 kg
UTILITIES	
Power supply	L1/N/PE; 100–240 VAC; 50/60 Hz

All figures: WIPOTEC, HC-M-WD checkweigher technical data¹

Small numbers point to the sources listed below. Values are copied as printed, then converted to the unit shown.

Key features

- IP69K protection class for all components
- Hygienic stainless steel construction with stainless servo motors
- Stainless steel weigh cell with sloping housing
- Optional cleaning program for cleaning during operation
- Up to 250 pcs/min maximum output

Formats and options

Options cleaning mode

Details from sources^{1,2}

Sources

¹ WIPOTEC GmbH, HC-M-WD checkweigher technical data, retrieved 2026-10-01

² WIPOTEC GmbH, HC-M-WD checkweigher product page, retrieved 2026-10-01